

# ABUS EasyLook Camera

Art.-Nr. PPDF17520X

Seite 1 von 2

## Technical data - ABUS EasyLook Camera

Base event	PIR & Software + Motion Mask
Channel width	20 MHz
Colour	Black
Compatible with	PPDF17000
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
DC voltage supply	12 V
Day/night switching	Auto
Dimensions	(W x L x H) 61 x 161 x 77 mm
Encryption	WPA2
Focal length	4 mm
Frequency range	2,403 - 2,478 GHz
Horizontal viewing angle	82 °
Housing material	Plastic
IP protection class	66
IR LEDs	Yes
IR range (up to)	15 m
IR swivel filter	Yes
Image sensor	1/3" CMOS
Loudspeaker	Yes
Max. humidity	90 %
Max. operating temperature	50 °C
Max. resolution @ frame rate	2305 x 1296 @15fps
Microphone	Yes
Min. humidity	30
Min. operating temperature	-10 °C
Minimum illumination (IR)	0,1 lx
Minimum illumination (colour)	1 lx
Net weight	0,3 kg
Optical Wave Length	940 nm
PIR range	8 m
PIR viewing angle	85 °
Plug type	DC-plug: 5,5 x 2,1 mm
Power consumption	3,6 W
Private zones	4
Resolution modes	2305 x 1296 (3MP)

# ABUS EasyLook Camera



Art.-Nr. PPDF17520X

Seite 2 von 2

---

## Technical data - ABUS EasyLook Camera

Sensitivity	-88 dBm
Transmission power	20 dBm
Vertical viewing angle	42 °
Video bit rate	2Mbps
Video compression	H.264+
White balance	Auto
Wireless range	(Depending on installation) 20 - 50 m