

# WLX Pro Bridge Box Intrusion

Art.-Nr. ACPA00001

Seite 1 von 1



## Technologies

- Ideal for controlling electronic door and gate operators, door buzzers, elevators, barriers, rolling grilles, turnstiles
- Control unit for the wAppLoxx Pro Wall Reader
- High level of protection against tampering due to separate mounting from the reader unit in the secured interior area
- Arming and disarming of intrusion detection systems (intrusion variant)
- Encrypted AES 128-bit data transmission to the wAppLoxx Pro Wall Reader via BUS
- Encrypted AES 128-bit wireless data connection to the wAppLoxx Pro Control
- External input enables switching of a relay e.g. for switches, pushbuttons, ...
- Further jumper settings e.g. control of the 2nd relay in case of sabotage, mute circuit Wall Reader, pulse, delay, ...
- Industrial variant (standard ELS TK PC housing) for commercial use with IP66 protection class

## Technical data - WLX Pro Bridge Box Intrusion

|                     |  |
|---------------------|--|
| Area of application | Indoor                                       |
| Colour              | white  |
| Connections         | 1 external input                             |
| DC voltage supply   | 3 A / 12 V                                   |
| Dimensions          | 101 x 135 x 30 mm                            |
| Housing material    | PVC  |
| Item abbreviation   | WLX-PRO-BB-I                                 |
| Radio frequency     | 868,3 MHz                                    |
| Wireless range      | 30 m indoor use (100 m free field nominal) m |