

8-Channel PoE Network Video Recorder (NVR)

Art.-Nr. NVR10021P

Seite 1 von 4



Convenient commissioning

Setting up the cameras in the recorder is quick and safe thanks to the intuitive installation wizard. The clear menu allows quick and easy programming. All ABUS cameras are integrated via protocol.

Free choice when operating

The local menu of the live view is clearly laid out and self-explanatory. The recorder can also be accessed via web browser, ABUS CMS software or app.

ABUS Link Station

The ABUS NVRs support the ABUS Link Station service. This allows easy setup in the app. The NVR can be accessed from the Internet without complex port forwarding. The service also offers a solution if only one IPv6 Internet address is available at the location.

Efficiency in everyday life

Fast and secure access control via the connectable ABUS licence plate recognition camera. A lot of time can be saved in the event of an incident: The integrated motion detection with object recognition (human/vehicle) enables a structured and efficient search of events, even for older ABUS IP cameras (see compatibility list).

Technologies

- Live view and recording of up to 8 IP cameras @ 8 MPx (4K)
- High-performance network data throughput with up to 336 MBit/s (80 MBit/s in / 256 MBit/s out)
- Integrated PoE switch (max. 150 watts) for power supply and fast commissioning of IP cameras
- Simple operation locally on the device, via web browser, ABUS CMS software or app
- Processing of the VCA function of ABUS IP cameras for precise detection and differentiation of people and vehicles in real time
- Manual or controlled recording according to schedule, motion detection, alarm input or VCA
- Recording on up to 2 SATA hard drives for extensive and reliable storage of video data

8-Channel PoE Network Video Recorder (NVR)

Art.-Nr. NVR10021P

Seite 2 von 4

Technical data - 8-Channel PoE Network Video Recorder (NVR)

AC voltage supply	100 V
AHD video channels	0
Alarm inputs (NO/NC)	4
Alarming	Acoustic warning signal, OSD signal, email, CMS, alarm output, app push
Analogue video channels	0
Audio	Line In: 1 x Cinch (2.0 V s-s, 1000 Ω) – for network transmission only, Audio Out: 1 x Cinch (1000 Ω)
Audio compression	G.711ulaw / G.711alaw / G.722 / G.726 / AAC / MP2L2 / PCM
Battery - GRS type	CR1220
Battery - quantity	1
Camera inputs	8
Compatible with ABUS Link Station	Yes
Compatible with Secoris	No
Compatible with wAppLoxx Pro	No
Connections	1 x HDMI, 1 x VGA, 2 x RJ45 LAN, 8 x camera input (PoE), 1 x audio input (Cinch), 1 x audio output (Cinch), 1 x USB 3.0, 1 x USB 2.0, 1 x BNC output, 1 x DC input, 4 x alarm input, 1 x alarm output
Control	USB mouse, IP network via Internet browser/ABUS CMS
DDNS	Yes
Dimensions	380 x 315 x 50 mm
Event memory	Yes
Gross weight	3,7 kg
HD-CVI video channels	0
HD-SDI video channels	0
HD-TVI video channels	0
HDMI Out	Yes
Height	50 mm
Housing material	metal
Hybrid-capable	No
IP video channels	8
Installation type	Table, 19 inch rack (Note: fan integrated in recorder)
Length	315 mm
Loi Sarkozy compliant (only valid for FR)	Yes
Max. humidity	90 %
Max. operating temperature	55 °C
Min. display resolution	1024 x 768 Pixel

8-Channel PoE Network Video Recorder (NVR)

Art.-Nr. NVR10021P

Seite 3 von 4

Technical data - 8-Channel PoE Network Video Recorder (NVR)

Min. operating temperature	-10 °C
Mobile access	ABUS Link Station Lite / Pro (Apple iOS & Android)
Monitor outputs	1 x VGA, 1 x HDMI
Multi-monitor function	Yes
NTP	Yes
Net weight	1,8 kg
Network access	8 x RJ45 PoE (IEEE 802.3 af/at, max. 150 W) + 2 x RJ45 10/100/1000 Mbps
Network cameras	ABUS network cameras, 3rd party (abus.com), RTSP, Open Network Video
Network functions	Live view, playback, data export, settings
Network protocols	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, ABUS Server, NTP, RTSP, SMTP, SNMP, HTTP, HTTPS
Number of HDDs	2
Number of channels	8
Number of users	32
OSD language	DE, EN, FR, NL, DK, IT, ES, SE, PL
Other functions	Via NVR: 8 channel authorisation. (ABUS cameras from 2022, person/vehicle, see compatibility list)
PSTI conformity given	Yes
PSTI conformity required	Yes
PTZ control	Over IP network
Performance decoding (local live view & playback)	AI in NVR off: max. 64 MPx, AI over NVR: max. 40 MPx
PoE power total	150 W
PoE standard	802.3 at (PoE+)
Power consumption	2.200 mA
Power consumption incl. HDD	190 W
Pre/post alarm memory	Yes (pre-alarm depends on resolution and bitrate, post-alarm (5 - 600 sec.))
Product security updates at least until	2026-08-01
RAID	No
RS-485 interface	No
Recording modes	Manual, Schedule, Motion Detection, Alarm Input, VCA
Recording resolution @ frame rate per camera	32 MPx, 24 MPx, 12 MPx, 8 MPx, 6 MPx, 5 MPx, 4 MPx, 3 MPx, 1080p, 720p, VGA @ 25 fps
Relay output	1 (load capacity: 12 V DC/1 A)
Resolution HDMI output	HDMI V1.4, 4K(3840x2160)/60Hz, 4K(3840x2160)/30Hz, 1920x1080/60Hz, 1600x1200/60Hz, 1280x1024/60 Hz, 1024x768/60 Hz
Resolution VGA output	1920x1080p/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Search modes	Event, Date & Time, Smart Search, VCA
Simultaneous network access	128 camera connections

8-Channel PoE Network Video Recorder (NVR)

Art.-Nr. NVR10021P

Seite 4 von 4

Technical data - 8-Channel PoE Network Video Recorder (NVR)

Storage	1 x USB 2.0, 1 x USB 3.0
Storage medium	2 x SATA HDD (up to 16 TB per HDD)
Technology	IP
Total frame rate	200 fps
Total network throughput (input/output)	336 MBit/s (80 MBits/256 MBits)
Total video channels	8
User levels	3
Video Content Analysis (VCA)	Yes
Video compression	H.264, H.265 (incl. Dynamic GOP)
Views	1 / 4 / 6 / 8 / 9
Web server	Yes
Width	380 mm