Smartvest Pro wireless water detector



Art.-Nr. FUWM45000 Seite 1 von 2



Monitoring for protection against water damage in the cellar and other locations
When this discreet tool comes into contact with water from a faulty device or broken pipe, it reports it immediately.
The Smartvest Pro control panel then sounds a high-volume alarm and all connected users receive a push notification

The sensitive records in the cellar, the valuable systems in the technology room or all the floors and furnishings in the kitchen and living area: aren't we all always a bit nervous when we think of unexpected water damage occurring in these rooms? The Smartvest Pro wireless water detector provides a solution. As soon as the compact detector comes into contact with water, all connected users receive a push notification through the Smartvest Pro app. The Smartvest

Whether it's from a leak in the washing machine, dishwasher or water tank, an overflowing shower or bathtub or a broken water pipe, the Smartvest Pro wireless water detector is there to keep watch around the clock. Even when you've disarmed the Smartvest Pro security system's intruder alarm while you're home. The detector's battery is long-lasting and easy to replace. For a comfortably secure home. For you and your family.

Technologies

- Placed in the kitchen, technical room, cellar etc., Smartvest Pro wireless water detectors reliably detect and report accumulations of water
- For protection against water damage

through the Smartvest Pro app.

- Triggers the alarm and starts all the custom scenarios configured in combination with the Smartvest Pro wireless alarm system
- Simply place on the surface you want it to monitor

Pro control panel also immediately issues a high-volume alarm.

Includes easily replaceable battery



Smartvest Pro wireless water detector

Art.-Nr. FUWM45000 Seite 2 von 2

Technical data - Smartvest Pro wireless water detector

Wireless range	Depending on installation max. 100 m
Transmission power	11,3 dBm
Standby power consumption	0,01 mA
Radio modulation	FSK
Radio frequency	868,3 MHz
Net weight	0,046 kg
Min. operating temperature	0 °C
Min. humidity	10 %
Max. operating temperature	40 °C
Max. humidity	90 %
Housing material	Plastic
Gross weight	0,077 kg
Dimensions	Ø 65 x 25 mm
Colour	white
Battery type	Replaceable
Battery - type	CR2032 (3V)
Battery - quantity	1
Battery - max. battery life	2 y
Battery - battery operation	Yes
Area of application	Interior