

24-Port PoE Gigabit Switch Managed

Art.-Nr. ITAC10131

Seite 1 von 2

This compact switch offers 24 connections with 10/100/1000 Mbit/s and is particularly suited for projects using ABUS products. For a convenient and secure installation, the switch can be built into a rack.

For more detailed information, visit the manufacturer's website at a [class="link" href="http://www.hp.com/www.hp.com/a"](http://www.hp.com/www.hp.com/a).

Technologies

- Connections: Gigabit PoE (downstream), 1 x Gigabit (uplink) RJ45, 1 x Gigabit (uplink) SFP
- Supports PoE and PoE+ (IEEE 802.3 af/at)
- Supports web-based network management and PoE management
- Display of PoE power consumption for each port in the web browser
- 6 KV overvoltage protection reduces the risk of failure and damage
- Port isolation, PoE watchdog, link aggregation/port bundling, loop prevention/loop avoidance
- Suitable for professional installation in a 19 inch rack

Technical data - 24-Port PoE Gigabit Switch Managed

AC power supply	100 - 240 V
Application purpose	General surveillance
Connections	24 x Gigabit PoE port, 1 x Gigabit RJ45 port, 1 x Gigabit SFP port
Depth	221 mm
Dimensions	(L x W x H) 221 x 440 x 44 mm
Gross weight	3.5 kg
Height	44 mm
Housing material	Metal
Language Manual	DE, GB, FR, NL, DK, IT
Language Packaging	DE, GB, FR, NL, DK, IT
Length	221 mm
Max. Air humidity	95 %
Max. Operating temperature	45 °C
Max. PoE power per port	30 watts (note total PoE power)
Min. operating temperature	0 °C
Net weight	2.82 kg
Network connection	Downstream: 16x 10/100/1000Base-T (PoE), Uplink: 1x 10/100/1000Base-T, 1 x SFP
Network standards	IEEE 802.3 af/at, IEEE 802.1Q, IEEE 802.1D STP, IEEE 802.1w RSTP, IEEE 802.1ab LLP
Other functions	Port Isolation, PoE Watchdog, 6 KV Surge Protection, Link Aggregation, Loop Prevention, VLAN, Port Bandwidth, PoE Power Consumption, Port Mirror
PSTI conformity given	Yes
PSTI conformity needed	Yes
Pin assignment Power supply	1/2(-), 3/6(+), 4/5(+), 7/8(-)

24-Port PoE Gigabit Switch Managed

Art.-Nr. ITAC10131

Seite 2 von 2

Technical data - 24-Port PoE Gigabit Switch Managed

PoE Standard	IEEE 802.3 af/at
Power consumption	400 W
Product group	Accessories
Product security update min until	2026-10-01
Total PoE power	370 W
WEEE group	09
width	440 mm