

SmartLook Battery outdoor camera with Pan and Tilt function

Art.-Nr. PPIC92500X

Seite 1 von 3

Technologies

- Smart, wireless pan-and-tilt security camera with a removable battery and solar panel for off-grid operation
- Flexible and easy to install in places without a power supply – ideal for the home, garage, garden or driveway
- Pan and tilt for an extra-wide field of view, plus a home position and two customizable presets for quickly switching between saved viewing angles
- Set up in just a few minutes: the app wizard guides you through the installation step by step. Free access to live streams, storage, features and personal settings
- Sharp 2K resolution and reliable night vision deliver clear, detailed images day and night
- Smart motion detection reliably distinguishes between people, animals and vehicles, and reduces false alarms
- The siren and two-way audio system enable active deterrence and direct communication with visitors
- Convenient charging via a solar panel for reliable and independent operation
- Local storage on a microSD card (not included) for simple and reliable recording
- Compatible with Smartvest Pro and ABUS One

Technical data - SmartLook Battery outdoor camera with Pan and Tilt function

Air humidity	10% – 90% (non-condensing)
Aperture	F 2.0
App	ABUS App2Cam Plus
Application purpose	General surveillance
Areas of application	Outdoor
Article program	Comfort
Audio	Two-way audio
Audio compression	AAC
Audio input	Microphone
Audio output	Loudspeaker
Battery - battery operation	Yes
Battery - permanently installed	No
Battery - quantity	1
Camera type	Pan/tilt dome
Colour	white, black
Compatible with ABUS Link Station	No
Compatible with Comfion	No
Compatible with Secoris	No
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No

SmartLook Battery outdoor camera with Pan and Tilt function

Art.-Nr. PPIC92500X

Seite 2 von 3

Technical data - SmartLook Battery outdoor camera with Pan and Tilt function

Compatible with wAppLoxx Pro	No
Connections	1 x USB-C (charging)
Controllable with app	Yes
Day/night switching	Automatic
Depth	175 mm
Encryption	AES 128bit, WPA/WPA2-PSK/WPA3 Personal
Frequency range	2,4 / 5,8 GHz
Gross weight	1.86 kg
Height	165 mm
Horizontal viewing angle	85 °
IR LEDs	Yes
IR swivel filter	Yes
Image sensor	1/3" Progressive Scan CMOS
Language Manual	DE, EN, FR, NL, DK, IT, PL, ES
Language OSD	DE, EN, FR, NL, DK, IT, PL, ES
Language Packaging	DE, EN, FR, NL, DK, IT, PL, ES
Lens	Fixed
Loudspeaker	Yes
Max. Resolution @ frame rate	2560 × 1440 @ 15 fps
Max. operating temperature	50 °C
Min. operating temperature	-10 °C
Motion detection	Yes, 3 configurable zones
Mounting location	Wall, Ceiling
Mounting type	Surface mounted
Net weight	0.905 kg
Network protocols	P2P
Number of IR LEDs	4
Number of presets	3
Number of simultaneous accesses	2
Pan/tilt range	340° horizontal / 80° vertical
Power supply	Solar, Rechargeable battery
Privacy zones	Yes
Rechargeable battery type	Li-Ion-Akku, 3,6 V / 9600 mAh
Resolution	2560 x 1440 Pixel
Storage medium	microSD card (up to 256 Gbyte, not included)
Vertical angle of view	45 °
Video bitrate	Max. 2 Mbit/s

SmartLook Battery outdoor camera with Pan and Tilt function

Art.-Nr. PPIC92500X

Seite 3 von 3

Technical data - SmartLook Battery outdoor camera with Pan and Tilt function

Video compression	H.264+
Video motion detector included	Yes
Width	97 mm