SmartLook battery-powered outdoor camera

Art.-Nr. PPIC92000X

Technologies

- Smart, wireless outdoor camera with a built-in battery and solar panel for flexible monitoring without the need for a mains power supply
- Flexible and easy to install in places without a power supply – ideal for the home, garage, garden or driveway
- Ideal for targeted surveillance of entrances, paths and access roads thanks to its 85° field of view
- Set up in just a few minutes: the app wizard guides you through the installation step by step. Free access to live streams, storage, features and personal settings
- Sharp 2K resolution and reliable night vision deliver clear, detailed images day and night
- Smart motion detection reliably distinguishes between people, animals and vehicles, and reduces false alarms
- The siren and two-way audio system enable active deterrence and direct communication with visitors
- Convenient charging via a solar panel for reliable and independent operation
- Local storage on a microSD card (not included) for simple and reliable recording
- Compatible with Smartvest Pro and ABUS One

Technical data - SmartLook battery-powered outdoor camera

Air humidity	10% – 90% (non-condensing)
Aperture	F 2.0
App	ABUS App2Cam Plus
Application purpose	General surveillance
Areas of application	Outdoor
Article program	Comfort
Audio	2-way audio
Audio compression	AAC
Audio input	Microphone
Audio output	Loudspeaker
Battery - battery operation	Yes
Battery - quantity	1
Camera type	Tube
Colour	white, black
Compatible with ABUS Link Station	No
Compatible with Comfion	No
Compatible with Secoris	No
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
Compatible with wAppLoxx Pro	No

Subject to technical modifications. We assume no liability for mistakes and printing errors. © ABUS 11/2026

SmartLook battery-powered outdoor camera

Technical data - SmartLook battery-powered outdoor camera

Connections	1 x USB-C (charging)
Controllable with app	Yes
Day/night switching	Automatic
Depth	169 mm
Encryption	AES 128bit, WPA/WPA2-PSK/WPA3 Personal
Frequency range	2,4 / 5,8 GHz
Gross weight	1.319 kg
Height	91 mm
Horizontal viewing angle	85 °
IR LEDs	Yes
IR swivel filter	Yes
Image sensor	1/3" Progressive Scan CMOS
Language Manual	DE, EN, FR, NL, DK, IT, PL, ES
Language OSD	DE, EN, FR, NL, DK, IT, PL, ES
Language Packaging	DE, EN, FR, NL, DK, IT, PL, ES
Lens	Fixed
Loudspeaker	Yes
Max. Resolution @ frame rate	2560 × 1440 @ 15 fps
Max. operating temperature	50 °C
Min. operating temperature	-10 °C
Motion detection	Yes, 3 configurable zones
Mounting location	Wall, ceiling
Mounting type	Surface mounted
Net weight	0.342 kg
Network protocols	P2P
Number of IR LEDs	2
Number of simultaneous accesses	2
Power supply	Rechargeable battery, Solar
Privacy zones	Yes
Protection class IP	65
Rechargable battery type	Rechargeable Li-ion battery, 3.6 V / 6000 mAh
Resolution	2560 x 1440 Pixel
Storage medium	microSD card (up to 256 Gbyte, not included)
Vertical angle of view	45 °
Video bitrate	Max. 2 Mbit/s
Video compression	H.264+
Video motion detector included	Yes

Subject to technical modifications. We assume no liability for mistakes and printing errors. © ABUS 11/2026

SmartLook battery-powered outdoor camera

Technical data - SmartLook battery-powered outdoor camera

Width	58 mm

Subject to technical modifications. We assume no liability for mistakes and printing errors. © ABUS 11/2026