



## Technologies

- According to DIN EN 1906 SK 1 and DIN 18 257 ES 0
- Integrated pulling protection with cylinder cover plus freely rotating special steel disc
- Increased leverage resistance: solid cams plus inner screws
- Proven layered construction: hardened steel bottom plate, plus sturdy cover plate
- HLN ZS: Spacing: 92 mm, square bolt: 10 mm
- KLN ZS: Spacing: 72 mm, square bolt: 8 mm

## Operation and use

- For main entrance doors (HLN) and apartment doors (KLN)
- Grip plate outside, handle inside
- HLN: Suitable for door thicknesses of 52 - 67 mm
- KLN: Suitable for door thicknesses of 37 - 47 mm
- Mounting material for deviating door thicknesses can be supplied

## Variants

- Finish: F2 (silver anodized)
- Alternatively available as a handle/handle set

## Technical data - HLN414 ZS F2 CL/DFNLI

|                             |            |
|-----------------------------|------------|
| Beidseitig Drücker          | No         |
| Cylinder protrusion         | 10 - 18 mm |
| Distance measure            | 92 mm      |
| Door fitting for fire doors | No         |
| Door type                   | Entry door |

# HLN414 ZS F2 CL/DFNLI

Seite 2 von 2

## Technical data - HLN414 ZS F2 CL/DFNLI

|                              |                            |
|------------------------------|----------------------------|
| Interchangeable fitting      | Yes                        |
| Security Level Home Security | 6                          |
| Weight                       | 1240 g                     |
| colour                       | F2: Aluminum Nickel Silver |
| pulling protection           | Yes                        |
| EAN                          | 4003318203695              |

## Technical drawing

