



The compact alarm is the all-in-one module from ABUS Security-Center. You can install this combination signalling device inside and outside your building. Signals between the alarm center and the accessory module can be wireless or by cable to a wired alarm panel. The compact alarm module is a combination signalling device. In the event of an alarm, the alarm sounder generates an extremely loud signal tone with over 118 dB sound pressure. The alarm duration - 3 minutes or 20 minutes - is programmable. In addition to the audible alarm, there is an optical alert from a red Xenon strobe light that is visible over long distances (flash frequency: 1 Hz). The alarm sounder and the strobe light can be controlled separately. The robust, waterproof housing of galvanised steel (IP 34) is protected from tampering by wall and lid contacts. The compact alarm module is supplied externally with 12V operating voltage. Power consumption in standby mode is 50 mA, and in alarm mode 480 mA.

## Technologies

- Rugged, weatherproof outdoor siren
- Multiply monitored for tampering
- Xenon flasher
- Optional backup battery
- Sound pressure: 116 dB(A) @ 1 m
- Protection class IP34

## Technical data - Compact Alerting

Backup power supply	1200 mAh rechargeable battery (BT2012) optional
DC voltage supply	12 V
Dimensions	(WxHxD) 315x200x50 mm
Flashing frequency	1 Hz
Height	200 mm
Housing material	Steel

## Technical data - Compact Alerting

IP protection class	34
Installation location	Indoors and protected outdoor areas
Length	50 mm
Light source	Xenon
Luminous colour	Red
Max. operating temperature	55 °C
Min. operating temperature	-25 °C
Net weight	2,45 kg
Power consumption	430 mA
Sabotage monitoring	Wall/cover contact and cable
Sound pressure	116 dB
VdS class	none
Voltage monitoring	Yes
Width	315 mm