

Door Opening Detector, 2 m, 4-core

Art.-Nr. MK4000

Seite 1 von 2



The door opening detector is a magnetic contact for protecting large (garage) doors. Unauthorised opening is detected and reported to the alarm panel. The door opening detector is mounted chiefly on roll-up, sliding, and up-and-over doors. The detector consists of a magnetic contact (reed) and a magnet. These are fitted parallel to each other. The electric circuit of this NC opening detector is normally closed (NC). If the distance between reed and magnet increases, the circuit is broken and an alarm reported. The detector is tamper-protected. The best installation location is in the middle of the entrance. The magnetic contact is mounted on the ground and the magnet on the inside of the door at a distance of about 20 mm. The door opening detector is perfectly suited for surface-fitting. It is absolutely water and dust-proof (IP 68). Its extremely robust aluminium housing protects it from damage even when driven over.CRLF

Technologies

- Magnetic contact for installation and assembly
- NC switching contact
- 2 m cable / 4-wire

Technical data - Door Opening Detector, 2 m, 4-core

Cable length	2 m
Cable type	4-core
Colour	other
Compatible with	Secoris, Secvest, Terxon
Connections	NC, max. contact capacity 60 V DC/AC/1 A/10 W
Dimensions	(WxHxD) 180x14x45 mm
External field protection	No
Height	230 mm
Housing material	Aluminium
IP protection class	65
Installation location	Setup, optimal triggering clearance 20 mm
Installation type	Surface mounting
Length	45 mm
Max. operating temperature	50 °C
PSTI conformity required	No

Door Opening Detector, 2 m, 4-core

Art.-Nr. MK4000

Seite 2 von 2

Technical data - Door Opening Detector, 2 m, 4-core

Sabotage monitoring	Yes
Sensor type	Reed contact
Type of detection	Magnetic field measurement
Width	13 mm