

Secvest Wireless Magnetic Contact FSL (white)

Art.-Nr. FUMK50010W

Seite 1 von 2

Reliable alarm triggering in the event of intrusion

The wireless opening detector detects and reports the unauthorised opening of doors and windows using a magnetic contact. In the event of an incident, it informs the wireless alarm panel, which then triggers the corresponding set alarm.

Detection and notification

The product consists of a detector and a magnet. These components are mounted parallel to each other on the moving part of the window or door and on the window or door frame. The detector triggers as soon as the distance between the two contact points is increased when the window or door is opened. To ensure that a window can still be tilted when the wireless magnetic contact is closed, it can also be mounted on the lower window frame.

Even more protection with additional wired alarm zones

The wireless opening detector also allows wiring with additional detectors that effectively extend the intrusion protection. The detector can be connected to a passive glass break alarm, for example, which can be mounted to the window pane and detects window breakages. The wireless opening detector for the Secvest wireless alarm system is available in white and brown.

Technologies

- Reliably detects opening of windows and doors
- Connection option for additional wired detectors
- Can be used as a wireless module
- Tamper monitoring

Technical data - Secvest Wireless Magnetic Contact FSL (white)

Battery - max. battery life	2 years(s)
Battery type	3V CR2 Li/MnO ₂
Certifications	VdS home, EN 50131 Grade 2
Color options	white, brown
Colour	white
Compatible with	Secvest, Terxon, BUM060040
Connections	Screw terminal (FSL)
Current consumption	30 mA
DC power supply	3 V
Detection method	Magnetic field measurement
Dimensions	(WxHxD) 33x89x29 mm
Environmental class	I
Height	89 mm

Secvest Wireless Magnetic Contact FSL (white)

Art.-Nr. FUMK50010W

Seite 2 von 2

Technical data - Secvest Wireless Magnetic Contact FSL (white)

Housing material	ABS
Length	29 mm
Max. Operating temperature	55 °C
Max. Transmit range (free field)	100 m
Max. Transmitting range (building)	30 m
Mechanical protection	No
Min. operating temperature	-10 °C
Modulation	FM
Mounting location	Windows, doors
Net weight	0.076 kg
PSTI conformity needed	No
Power consumption	0.09 W
Product group	Detectors
Radio frequency	868.6625 MHz
Radio networked	Yes
Radio power	10 mW
Security gradient	2
Sensor type	Reed contact
Status display	Yes
Tamper monitoring	Yes
Technology	Electronics
Type of protection	Intrusion protection
VdS class	other
Voltage monitoring	Yes
WEEE group	09
Width sensor	33 mm
width	33 mm