

Secvest Mini Wireless Magnetic Contact (brown)

Art.-Nr. FUMK50020B Seite 1 von 2



Unobtrusive and reliable securing of windows and doors

The Secvest mini wireless opening detector is especially compact and discreet. It consists of a detector and a magnet. These components are mounted parallel to each other on the moving part of the window or door and on the window or door frame. The detector triggers as soon as the distance between the two contact points is increased when the window or door is opened and informs the alarm panel. The Secvest mini wireless opening detector is available in white, brown and silver.

Technologies

- Compact, discreet design
- Reliably detects opening of windows and doors
- Tamper monitoring

Technical data - Secvest Mini Wireless Magnetic Contact (brown)

| Battery - max. battery life | 3 y |
|-----------------------------|----------------------------|
| Battery - quantity | 1 |
| Battery - type | 3.6 V Lithium 1/2 AA |
| Certifications | compliant to EN 50131-1 |
| Colour | brown |
| Compatible with | Secvest, Terxon, BUM060040 |
| DC voltage supply | 3,6 V |
| Dimensions | (WxHxD) 28x42x18 mm |
| Environmental class | |
| Gross weight | 0,09 kg |
| Height | 42 mm |
| Housing material | ABS |



Secvest Mini Wireless Magnetic Contact (brown)

Art.-Nr. FUMK50020B Seite 2 von 2

Technical data - Secvest Mini Wireless Magnetic Contact (brown)

| Installation location | Windows, doors |
|-------------------------------|------------------------|
| Language of instructions | DE, UK, FR, NL, DK, IT |
| Length | 18 mm |
| Max. operating temperature | 55 °C |
| Max. transmission range | 30 m |
| (building) | |
| Max. transmission range (free | 100 m |
| field) | |
| Min. operating temperature | -10 °C |
| Modulation | FM |
| Net weight | 0,06 kg |
| PSTI conformity required | No |
| Radio frequency | 868 MHz |
| Radio power | 10 mW |
| Sabotage monitoring | Yes |
| Security level | 2 |
| Sensor type | Reed contact |
| Status display | Yes |
| Type of detection | Magnetic switch |
| VdS class | none |
| Voltage monitoring | Yes |
| Width | 28 mm |