

Secvest Mini Wireless Magnetic Contact (silver)

Art.-Nr. FUMK50020S

Seite 1 von 2

Discreet and secure protection for windows and doors

The Secvest Mini wireless opening detector is particularly small and unobtrusive. It consists of a detector and a magnet. These components are mounted parallel to each other on the moving part of the window or door and on the window or door frame. The detector triggers as soon as the distance between the two contact points is increased when the window or door is opened and informs the alarm panel. The Secvest Mini wireless opening detector is available in different colours.

Technologies

- Compact and discreet design

Technical data - Secvest Mini Wireless Magnetic Contact (silver)

Battery - max. battery life	3 years(s)
Battery - quantity	1
Battery type	3.6 V Lithium 1/2 AA
Certifications	compliant to EN 50131-1
Color options	white, brown, silver
Colour	silver
Compatible with	Secvest, Terxon, BUM060040
DC power supply	3,6 V
Detection method	Magnetic switch
Dimensions	(WxHxD) 28x42x18 mm
Environmental class	I
Gross weight	0.09 kg
Height	42 mm
Housing material	ABS
Language Manual	DE, UK, FR, NL, DK, IT
Length	18 mm
Max. Operating temperature	55 °C
Max. Transmit range (free field)	100 m
Max. Transmitting range (building)	30 m
Mechanical protection	No
Min. operating temperature	-10 °C
Modulation	FM
Mounting location	Windows, doors
Net weight	0.01 kg

Secvest Mini Wireless Magnetic Contact (silver)

Art.-Nr. FUMK50020S

Seite 2 von 2

Technical data - Secvest Mini Wireless Magnetic Contact (silver)

PSTI conformity needed	No
Product group	Detectors
Radio frequency	868.6625 MHz
Radio networked	Yes
Radio power	10 mW
Security gradient	2
Sensor type	Reed contact
Status display	Yes
Tamper monitoring	Yes
Technology	Electronics
Type of protection	Intrusion protection
VdS class	none
Voltage monitoring	Yes
WEEE group	09
Width sensor	28 mm
width	28 mm