

Secvest Wireless Outdoor Siren Kit

Art.-Nr. FUSG50020

Seite 1 von 3



The Secvest wireless outdoor siren kit consists of a compact sounder and the universal module. You can install the siren kit inside or outside a building. Signal transmission from the universal module to the alarm panel is wireless; the universal module and the siren are connected via cable. Alarming is done by the combination siren. In the event of an alarm, the siren produces an extremely loud sound with more than 116 dB sound acoustic pressure. The alarm duration is 3 minutes. In addition to the acoustic alarm a widely visible alarm is produced by the red Xenon flash light (flash frequency 1 Hz). Siren and flash can be controlled separately. The sturdy, weather-resistant housing made of galvanized steel (IP34) is protected against sabotage by a wall contact tamper switch. An emergency battery pack (1200 mAh) is already integrated in the housing. This backup power supply also triggers an alarm in the event of attempted sabotage, e.g. if cables are manipulated. The compact sounder module is powered by 12 V. The power consumption in standby mode is 50 mA, in the event of an alarm 480 mA.

Technologies

- Rugged, weatherproof outdoor siren
- Recommended if the signal volume is too low in outdoor areas
- Xenon flasher technology
- Mains and backup power

Technical data - International Switching-Mode Power Supply 13,8 V/1,75 A (Cord)

| | |
|-------------------|-----------------------------------|
| AC voltage supply | 100 - 240 V |
| Cable length | 1,5 m |
| DC voltage supply | 13,8 V |
| Dimensions | (W x H x D) about 46 x 80 x 38 mm |
| Housing material | ABS (white) |
| Input voltage AC | 230 V |
| Max. humidity | 90 % |

Secvest Wireless Outdoor Siren Kit

Art.-Nr. FUSG50020

Seite 2 von 3

Technical data - International Switching-Mode Power Supply 13,8 V/1,75 A (Cord)

| | |
|----------------------------|---------------|
| Max. operating temperature | 40 °C |
| Min. operating temperature | 0 °C |
| Net weight | 0,16 kg |
| Output voltage DC | 13,8 V |
| Power consumption | 1,75 mA |
| EAN | 4043158067521 |

Technical data - Wireless Universal Module

| | |
|--------------------------------------|---|
| Backup power supply | Yes |
| Battery - type | 6V DC, 1.2Ah |
| Compatible with | Secvest, Terxon |
| Connections | 4 x transistor relay (NO/NC), max. switch capacity 500 mA, 24 V DC, R=2 / 1 x RJ12 for control of the siren |
| DC voltage supply | 12 V |
| Depth | 42 mm |
| Dimensions | (WxHxD) 122x208x42 mm |
| Display | 10 LEDs |
| Height | 208 mm |
| Housing material | ABS |
| Length | 42 mm |
| Max. backup power supply duration | 12 h |
| Max. receiving range (building) | 30 m |
| Max. receiving range (free field) | 100 m |
| Max. transmission range (building) | 30 m |
| Max. transmission range (free field) | 100 m |
| Modulation | FM |
| Net weight | 0,33 kg |
| Power consumption | 70 mA |
| Radio frequency | 868 MHz |
| Radio power | 10 mW |
| Sabotage monitoring | Yes |
| VdS class | none |
| Voltage monitoring | Yes |
| Width | 122 mm |
| Zone closure | EOL, CC |

Secvest Wireless Outdoor Siren Kit

Art.-Nr. FUSG50020

Seite 3 von 3

Technical data - Wireless Universal Module

| | |
|-----|---------------|
| EAN | 4043158057614 |
|-----|---------------|

Technical data - Compact Alerting

| | |
|----------------------------|---|
| Backup power supply | 1200 mAh rechargeable battery (BT2012) optional |
| DC voltage supply | 12 V |
| Dimensions | (WxHxD) 315x200x50 mm |
| Flashing frequency | 1 Hz |
| Height | 200 mm |
| Housing material | Steel |
| IP protection class | 34 |
| Installation location | Indoors and protected outdoor areas |
| Length | 50 mm |
| Light source | Xenon |
| Luminous colour | Red |
| Max. operating temperature | 55 °C |
| Min. operating temperature | -25 °C |
| Net weight | 2,45 kg |
| Power consumption | 430 mA |
| Sabotage monitoring | Wall/cover contact and cable |
| Sound pressure | 116 dB |
| VdS class | none |
| Voltage monitoring | Yes |
| Width | 315 mm |
| EAN | 4043158013733 |