

Secvest Wireless Additional Door Lock with Rotary Knob - 7010 E (white)

Art.-Nr. FUFT50011W

Seite 1 von 2



Active intrusion protection for house doors

The Secvest wireless additional door lock with double-stroke bolts and outer and inner cylinder locks provides double protection for your door. The door is fitted with an additional mechanical lock featuring more than one tonne of resistance. The additional lock also detects attempts at opening, providing active intrusion protection.

Automatic disarming and arming of the alarm system

Something that's especially convenient: when the additional door lock is locked, the alarm panel is armed or disarmed automatically. A feedback tone immediately informs you about the status of the alarm system. The lock is available in white and brown.

Secure wireless communication

Thanks to a secure wireless communication procedure, this product is protected against 'replay attacks', as are the Secvest wireless alarm system and Secvest Touch alarm systems. This procedure for preventing third party tampering exceeds the requirements of the "DIN EN 50131-1 level 2" security standard.

Note: This product can only be used in combination with the FUAA5xxxx Secvest alarm control panel.

Technologies

- Active intrusion protection (immediately detects break-in attempts)
- Mechanical intrusion protection with more than one tonne of pressure resistance
- Double-stroke bolts with outer cylinder lock and inner rotary knob
- Suitable for doors with DIN right and DIN left hinges
- Communicates with the Secvest and Secvest Touch via a secure wireless connection

Technical data - Secvest Wireless Additional Door Lock with Rotary Knob - 7010 E (white)

Battery - max. battery life	1 y
Battery - type	2 x 1.5 V AAA batteries, Varta Industrial / Industrial Pro, Duracell Industrial, Panasonic Powerline
Colour	white
Colour options	white, brown
Compatible with	Secvest, BUM060040

Secvest Wireless Additional Door Lock with Rotary Knob - 7010 E (white)

Art.-Nr. FUFT50011W

Seite 2 von 2

Technical data - Secvest Wireless Additional Door Lock with Rotary Knob - 7010 E (white)

DC voltage supply	3 V
Dimensions	(WxHxD) 135x75x47 mm
Environmental class	II
Height	75 mm
Housing material	ABS, Stainless Steel
Installation location	Doors
Length	47 mm
Max. operating temperature	55 °C
Max. receiving range (building)	30 m
Max. receiving range (free field)	100 m
Max. transmission range (building)	30 m
Max. transmission range (free field)	100 m
Min. operating temperature	-10 °C
Modulation	FM
Net weight	1,138 kg
PSTI conformity required	No
Radio power	10 mW
Sabotage monitoring	Yes
Sensor type	Magnetic field sensor
Type of detection	Magnetic switch and magnetic field sensor
Voltage monitoring	Yes
Width	135 mm