

4x analog HD signal distributor

Art.-Nr. TVAC25240

Seite 1 von 1



Use the 4x analog HD signal distributor to transmit the video input signal without loss to four monitors. Connect your camera to the signal distributor's video input and connect the monitors to the video outputs. Four BNC video outputs are provided.

Technologies

- Supports high resolutions up to 8MPx (4K) without video loss
- Transmission of a video signal to up to four monitors or recorders
- Suitable for HD-TVI, AHD, HDCVI, 960H, NTSC, PAL
- Channel 4 supports HD video + data control signal (UTC - Up The Coax)

Technical data - 4x analog HD signal distributor

DC voltage supply	12 V
Dimensions	(W x H x D) 138 x 30 x 86 mm
Height	30 mm
Language of instructions	DE, GB
Language packing	DE, GB, FR, NL, DK, IT
Length	86 mm
Max. humidity	95 %
Max. operating temperature	55 °C
Min. operating temperature	0 °C
Net weight	0,14 kg
PSTI conformity required	No
Power consumption	110 mA
Video input	1 BNC
Video input impedance	75 Ω
Video input level	1 Vpp dB
Video output	4 BNC
Video output level	1 Vpp
Video system	HD-TVI, HD-CVI, AHD, 960H, NTSC, PAL
Width	138 mm