

# Secvest Wireless Remote Control

Art.-Nr. FUBE50013

Seite 1 von 2



## Convenient operation of the alarm control panel

The wireless remote control is a practical accessory for the Secvest wireless alarm system. Its use enables the system to be operated at the simple touch of a button. It also allows the current system status to be queried at any time.

## Reliable arming at long range

The remote control facilitates arming and disarming of the alarm system - even at great distances. Thanks to 8 integrated LEDs, real-time feedback is provided regarding changes to the system status. The transmission range is approx. 30 metres.

## Rapid assistance in an emergency

Simultaneously pressing the 'arm' and 'disarm' buttons triggers a panic alarm. This protects both people and valuables effectively.

## Display of additional information

By pressing the third button, important information about the status of the alarm control panel can be queried (armed, disarmed, internal protection active, fault). Feedback is immediately displayed on the remote control.

## Useful convenience functions

The fourth button allows custom configuration, it can be set to control a garage door, for example. This button can be programmed directly on the alarm control panel.

## Technologies

- User-friendly remote control with easily identifiable symbols
- Features 'arm', 'disarm' and 'status query' keys
- 8 LEDs provide an overview and display current system status

# Secvest Wireless Remote Control

Art.-Nr. FUBE50013

Seite 2 von 2

- Button for custom configuration available (Secvest wireless alarm system only)
- Optional manual panic alarm available (Secvest wireless alarm system only)

## Technical data - Secvest Wireless Remote Control

|                                      |                                    |
|--------------------------------------|------------------------------------|
| Battery - max. battery life          | 2 y                                |
| Battery - type                       | CR2450 3V Li-Mn (FU2987)           |
| Certifications                       | VdS home, REQ                      |
| DC voltage supply                    | 3 V                                |
| Dimensions                           | (WxHxD) 36,2 x 17 x 62 mm          |
| Display                              | LED                                |
| Environmental class                  | II                                 |
| Height                               | 17 mm                              |
| Housing material                     | ABS                                |
| Language of instructions             | DE, UK, FR, NL, DK, PL             |
| Language packing                     | DE, UK, FR, NL, DK, PL, ES, SE, IT |
| Length                               | 62 mm                              |
| Max. humidity                        | 75 %                               |
| Max. operating temperature           | 40 °C                              |
| Max. receiving range (building)      | 30 m                               |
| Max. receiving range (free field)    | 200 m                              |
| Max. transmission range (building)   | 30 m                               |
| Max. transmission range (free field) | 200 m                              |
| Min. operating temperature           | -10 °C                             |
| Modulation                           | FM                                 |
| Net weight                           | 0,035 kg                           |
| Radio frequency                      | 868,6625 MHz                       |
| Radio power                          | 10 mW                              |
| Security level                       | 2                                  |
| VdS approval no.                     | H 114001                           |
| VdS class                            | home                               |
| Voltage monitoring                   | Yes                                |
| Width                                | 36 mm                              |