

# Secvest Hybrid Module Set Power Supply

Art.-Nr. FUM050200

Seite 1 von 2



## Technical data - Secvest Hybrid Module Set Power Supply

|                          |                |
|--------------------------|----------------|
| Dimensions               | 460x360x350 mm |
| Gross weight             | 7,27 kg        |
| Height                   | 350 mm         |
| Length                   | 460 mm         |
| Net weight               | 7,07 kg        |
| PSTI conformity required | No             |
| Width                    | 360 mm         |

## Technical data - Secvest Hybrid Module

|                                      |                       |
|--------------------------------------|-----------------------|
| DC voltage supply                    | 10,5 - 15 V           |
| Dimensions                           | (LxWxH) 136x227x45 mm |
| Environmental class                  | II                    |
| Gross weight                         | 0,62 kg               |
| Height                               | 45 mm                 |
| Housing material                     | PC/ABS                |
| IP protection class                  | 30                    |
| Installation type                    | Surface mounted       |
| Language of instructions             | DE,EN,FR,NL,DK,IT     |
| Length                               | 227 mm                |
| Max. humidity                        | 75 %                  |
| Max. operating temperature           | 40 °C                 |
| Max. receiving range (free field)    | 500 m                 |
| Max. transmission range (free field) | 500 m                 |

# Secvest Hybrid Module Set Power Supply

Art.-Nr. FUM050200

Seite 2 von 2

## Technical data - Secvest Hybrid Module

|                            |                                                       |
|----------------------------|-------------------------------------------------------|
| Min. operating temperature | -10 °C                                                |
| Net weight                 | 0,48 kg                                               |
| Number of wired zones      | 10 x FSL/DEOL or 5 x CC                               |
| Outputs                    | 4 x Relays (max. 24 V AC rms or 30 V DC)              |
| PSTI conformity required   | No                                                    |
| Power consumption          | 100 mA                                                |
| Programming                | Directly at the alarm control panel or via web server |
| Radio frequency            | 868,6625 MHz                                          |
| Radio power                | 10 mW                                                 |
| Sabotage monitoring        | Yes                                                   |
| Transmission path          | Wireless                                              |
| Type of inputs             | Voltage                                               |
| Voltage monitoring         | Yes                                                   |
| Width                      | 136 mm                                                |
| EAN                        | 4043158144635                                         |

## Technical data - VdS Battery, 12 V, 7.2 Ah

|                          |                      |
|--------------------------|----------------------|
| Battery type             | Lead gel             |
| Capacity                 | 7,2                  |
| Certifications           | VdS                  |
| Charging cycles          | up to 1000           |
| DC voltage supply        | 12 V                 |
| Dimensions               | (WxHxD) 65x94x151 mm |
| Height                   | 94 mm                |
| Length                   | 151 mm               |
| Net weight               | 2,54 kg              |
| PSTI conformity required | No                   |
| VdS approval no.         | G 112110             |
| Width                    | 65 mm                |
| EAN                      | 4043158000634        |