



Areas of Application

Locks out power switches during maintenance. Ideal for lockout applications where more than one safety padlock must be attached.

Details


- Non-conductive nylon hasp
- Holds up to 6 padlocks
- Withstands up to 450 kg, yet weighs only 28 grams

Material

· Hasp and locking slide: Nylon

Dimensions

- A: 178 mm
- B: 41 mm
- C: 3,11 mm
- D: 9,6 mm
- E: 11 mm



Temperature Range

-30°C to +135°C



Chemical Resistance

All approved chemicals listed are based on the manufacturer's specified chemical resistance chart for plastic material only.

Chemical	Grade
Mineral lubricants	Resistant
Aliphatic hydrocarbons	Resistant
Aromatic hydrocarbons	Resistant
Gasoline	Resistant
Weak mineral acids	Resistant
Strong mineral acids	Conditionally resistant
Weak organic acids	Conditionally resistant
Strong organic acids	Not resistant
Oxidizing acids	Conditionally resistant
Weak bases	Not resistant
Strong bases	Not resistant
Trichloroethylene	Resistant
Perchloroethylene	Resistant
Acetone	Resistant
Alcohols	Resistant
Hot water (hydrolysis resistance)	Resistant
UV light and weather	Conditionally resistant

Legal Note

ABUS products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses.