



---

## Areas of Application

Locks out all industrial CEE plugs from 16A (3-pole) to 125A (5-pole). Prevents from putting the plug into the socket, therefore, energizing the machine.

---

## Details

- Universal use: one device covers all CEE plug sizes
- Lightweight, handy and space-saving
- Holds 1 padlock

---

## Material

- Body: Polycarbonate

---

## Dimensions

- Length: 55 mm
- Width: 39 mm
- Depth: 27 mm

---

## Temperature Range

- -50°C to +130°C (-58°F to +266°F)

---

## Flame Rating

- UL94HB

## Chemical Resistance

All approved chemicals listed are based on the manufacturer's specified chemical resistance chart for plastic material only. The results were determined at a room temperature of +20°C/+68°F. All data are subject to environmental variables and product features.

Chemical	Grade
Mineral lubricants	Resistant
Aliphatic hydrocarbons	Not resistant
Aromatic hydrocarbons	Not resistant
Gasoline	Resistant
Weak mineral acids	Resistant
Strong mineral acids	Conditionally resistant
Weak organic acids	Resistant
Strong organic acids	Conditionally resistant
Oxidizing acids	Conditionally resistant
Weak bases	Conditionally resistant
Strong bases	Conditionally resistant
Trichloroethylene	Resistant
Perchloroethylene	Resistant
Acetone	Resistant
Alcohols	Resistant
Hot water (hydrolysis resistance)	Resistant
UV light and weather	Resistant

## Legal Note

ABUS products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses.