



Areas of Application

Block access to ball valves during maintenance.

Details

- High-quality polypropylene, long-lasting, robust and non-conductive
- Two sizes for most common ball valves
- To hold one padlock
- Different holes to fix the valve handle by the padlock

Material

- Body: Polypropylene

Dimensions

- V442: Length: 135 mm Width: 104 mm Depth: 78 mm
- V448: Length: 305 mm Width: 221 mm Depth: 144 mm

Temperature Range

- Polypropylene: 0°C to 100°C (32°F to 212°F)

Chemical Resistance

All approved chemicals listed are based on the manufacturer's specified chemical resistance chart for plastic material only. The results were determined at a room temperature of +20°C/+68°F. All data are subject to environmental variables and product features.

Chemical	Grade
Mineral lubricants	Conditionally resistant
Aliphatic hydrocarbons	Conditionally resistant
Aromatic hydrocarbons	Conditionally resistant
Gasoline	Conditionally resistant
Weak mineral acids	Resistant
Strong mineral acids	Conditionally resistant
Weak organic acids	Conditionally resistant
Strong organic acids	Conditionally resistant
Oxidizing acids	Conditionally resistant
Weak bases	Resistant
Strong bases	Resistant
Trichloroethylene	Conditionally resistant
Perchloroethylene	Conditionally resistant
Acetone	Resistant
Alcohols	Resistant
Hot water (hydrolysis resistance)	Resistant
UV light and weather	Conditionally resistant

Legal Note

ABUS products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses.
